TITAN

ALMOST Rocket Science

Clean Air Cabinets

Designed for PCR and applications requirering Sterility better than Class 100

SCANLAF

TITAN

ALMOST Rocket Science

Introducing the Titan and Titan PCR...rocket power to a clean work station...
Titan and Titan PCR: Ultra clean environment, low Running costs, slim design, personal work stations.
Designed for most applications where sterility and clean air are the essentials.

Titan

Titan is a true vertical laminar flow cabinet providing sterility and portability, easy to place on existing worktables or benches and can be easily removed and stored when not in use.

True laminar airflow with sterile air better than class 100 eliminates the risk of contaminationof the samples and avoids cross-contamination whilst working, The high work opening front, the low noise level and excellent lighting with clear side windows in polycarbonate makes the Titan a pleasant work station for the operators. The low energy consumption and the digital control system combines convenience with savings on energy and expensive HEPA-filters. Excellent for microbiological work, cleansing the environment of allergens and particles down to 1 microns for use in the electronics and contact lens manipulation and many other applications were a clean air environment is essential. Optional ULPA-filters can be fitted as required by the electronics industry and for nanotechnology applications.

The optional electrically operated elevation stand makes the Titan an excellent work bench with excellent ergonomics for correct operator posture for either a sitting or standing position whilst working.

Specifications

Titan cat.no. 9.100.010.001	Unit	
Material		Pressure chamber in polyester coated steel. Table top, front, side and back wall in strong polycarbonate.
External dimensions (DxWxH)	mm	336x626x975
Working chamber (DxWxH)	mm	313x574x530
Downflow, (0,40 m/s)	m^3/h	300
Energy consumption/Effect	W	90
Sound level	dB(A)	52
HEPA filter, EN 1822, H-14		99,995 % MPPS
Prefilters, quality EU 3		ASHRAE 83
Weight	kg	25
Accessories		Electrical elevation stand working heights from 75 cm to 105 cm

Spareparts	For Titan and Titan PCR
9.000.010.006	Electrical elevation stand 700 -1000 mm for Titan, Titan PCR, Atlas and Sirius
9.000.019.009	Prefilter for Titan and Titan PCR
9.000.019.011	Spare HEPA H-14 filter for Titan, Titan PCR, HV-mini models, Atlas and Sirius

Titan

Airflow Pattern
Titan and Titan PCR



Easy operation

Easy prefilter exchange

Titan PCR

Titan PCR is compact work station and a true vertical laminar flow cabinet with built in UV-light and is easy to place on existing work tables and can be easily removed and stored when not in used.

UV-light ensures inactivation of RNA/DNA contaminants within a few minutes and is the safe way to reliable and consistent results during daily PCR procedures. True laminar air-flow with sterile air better than class 100 eliminates the risk of cross-contamination whilst working, ensures no contamination of the chamber, which allows the UV light to work efficiently, being directed closely towards the work table - full product protection over the entire working area can be valuable in other work as well as for PCR procedures.

The high work opening front, the low noise level and excellent lighting with clear side windows in polycarbonate and built in lighting, makes the Titan PCR a pleasant work station for the operator. The low energy consumption and the digital control system combines convenience with savings on energy and expensive UV- light tubes and HEPA-filters. The combination of UV-light and sterile air together with an easy to clean chamber in stainless steel, large work opening and maximum operator comfort make the Titan PCR a the best choice.

An optional electrical elevation stand will make an excellent work bench with excellent ergonomics for correct operator posture for either a sitting or standing position whilst working.

Specifications

Titan PCR cat.no. 9.100.010.011	**Unit**	
Material		Pressure chamber in polyester coated steel, Table top in stainless steel 304 Front, side and backwall UV-resistant in strong polycarbonate.
External dimensions (DxWxH)	mm	336x626x975
Working chamber (DxWxH)	mm	313x574x530
Downflow, (0,40 m/s)	m^3/h	300
Energy consumption/Effect	W	90
Sound level	dB(A)	52
HEPA filter, EN 1822, H-14		99,995 % MPPS
Prefilters, quality EU 3		ASHRAE 83
UV-light intensity		254/15
Weight	kg	40
Included		Lightning. Digital display with Hour counter, digitally adjustable fan, alarm for power failure and air flow speed
Options		Communication with CTS, dampers and extract blowers. USB-port with software for documention purposes

Slim design

Safety

Electrical elevation stand

Titan PCR